



BOSON

MONOPHONIC INTEGRATED AMPLIFIER



250 Wrms (8Ω) , 400 Wrms (4Ω) of type A+D



The Boson integrated hybrid monophonic amplifier

Our solution is unique. First it offers the best of what transistors and lamps can mutually offer; this translates into warmth, neutrality and power. Second, the Boson monophonic integrated has a modular card for for easy replacement of all its usable components making the system the first monophonic block ecologically minded HiFiamplifier in the world. Finally, it offer the best warranty in the industry.

The Boson has scaling capabilities and can be integrated into the majority of existing listening room configurations. This is giving you more options in the system choices. The control of all the amplifiers of the system can be done with the front buttons of one of the Boson, the others replicating on the one touched, or by remote control or computer program.

Eon Art amplifiers use only proven and tested technologies. Some of these originated in the medical, jet fighter and marine electronic worlds. We hope to be able to find our amplifiers in a growing number of yachts and prestigious residences.





About EON ART



Eon Art and the Boson are the creation and implementation of Mr. Stéphane Hautcoeur. Research and development began in France in 2008 and continued in Canada until 2022. These 14 years offer us the Boson integrated Hybrid Monophonic Amplifier.

Each amplifier implements a single amplification channel including also the preamplification stage. You connect your sources directly to the Boson blocs.

It also offers 20% more power (Watts) and twice the power reserve than its little brother the Quark amplifier; which gives it even more bottom. You can connect many Boson to the same source line with it's internal Lundahl splitter.

Eon Art Canada Inc. is the result of 2017 structure modification of Eon Art Haute Fidélité, founded in 2012 in France, for it's move to Canada.

The company is based in Chandler, Quebec, Canada and is in partnership with Art Logik an Electronics and scientific computing firm.

Music can be defined as the immediate and pure transmission of emotions through sound. The recognition of the finest detail must be done in a natural wayand the Boson of Eon Art makes it possible.







Front view: Simple and flexible design inspired by the yacht Lady M.

Cabinet finishing and assembly by Oracle Audio Technologies.




Top view: A shield that protects against most electromagnetic waves and a unique high gloss finish.



View 3/4: A 7 mm aluminum case on a semi-precious Labradorite stone base with a massive 19mm façade.




Rear view: A lock secures access to the rail system and the inside of the enclosure.





The only high-end A+D integrated amplifier in the world.

Experience unique musical emotions with this master-piece of computer science. A generous power at all levels of volume that retains a warm, Soft and transparent sound. Not only is this amplifier unique, it is revolutionary in its Sustainability and environmental aspects. In addition, it has the longest guarantee of his class.



First Class Design

Our casing won two prize in at the Montreal International Design contest. Taking out the cradle on its rail system you immediately notice a new architecture.

Made with expertise it is Intended to make music; not only to push sounds. The components are carefully selected and tested in order to recreate a hearing experience identical to what you would have experienced during the recording.







Neutrality



The capacitors used on the path of the audio signal are all audiophile quality and bear the brands of recognized suppliers such as Amtrans, Clarity, Duelund, Mundorf and Solen. Those used in the most sensitive places are shielded. We ensured that their quantity was adjusted to provide no phase rotation and to use multiple complementary models with a different sound signature in order not to exacerbate it. We thus avoid the usual problems with the use of capacitors and guarantee the utmost neutrality of their action on the music.

Exclusivity





Since 2018, Eon Art Canada is the only amplifier company that has managed to produce an architecture that optimize the selection of its components and the engineering of it's circuits with a supercomputer simulation-assisted design process which allows to optimize the value and the choice of components. This brute force computing process can't be done otherwise than by supercomputer as the 800 cores machine we have. This unique technology ensures that any improvement that can be achieved on a circuit is actually done.

This results in a tube sound, that is, with details, image, and emotions without being limited to high efficiency loudspeakers that would otherwise be needed. It is admited that, the great force exclusive to the Boson, is also to be able to drive loudspeakers with difficult behavior without the traditional compromises.







Ultra low distortion volume control



External power



Quality control







Amplifier volume level is controlled by a set of individual high stability, very high precision and medical grade, thin metal film resistors which are selected by transistors. The complete absence of relays and mechanical potentiometer, as well as the circuit topology guaranteed a rate of distortion lower than those offered by competitors volume controllers, without any other impact on the source seen by the amplifier stage or mechanical wear.

An optional external reserve power supply is availlable for this amplifier. It is connected by two ultra high quality ten wire cables with shielded chrome and cadmium metal alloy ten pins circular locking military connectors. It literally triple the power reserve of the Boson and bring even thighter bass and deeper silence.


Each printed circuit board is subjected to rigorous automated testing after welding its components using specific computerized analyzers. The equipment is then tested for endurance and stability for twenty-four hour at full power under the eye of a 64-channel M300 Acquisition Center. An Audio Precision analyzer is used to prove that each amplifier reproduces complex musical signals according to ultra-high restrictive standards that we have selected and the most rigorous in the industry. Of course we also listen to each Boson in a reference system. Each step of the assembly and qualitative process is documented and signed by the various stakeholders in a certificate to the owner located in the hardcover user manual.











BOSON 250W MONOPHONIC INTEGRATED AMPLIFIER

Brand Eon Art Model Boson

Integrated mono amplifier

Class A+D

Buffer Stage Audiophiles discrete AOP & regulators Gain

40.117 dB

0.052%

(6922 / 6H23N-EB)

iOS et Android, Linux

Built-inautomatic shutoff

Built-inautomatic shutoff

Built-inautomatic shutoff

(10) 2 main,8 internals

Natural convection

Rated Power (1kHz,120 VAC) 4Ω 400 Wrms, 8Ω 250 Wrms 91.153 dB

S/N ratio reference to rated output

Frequency response 20 Hz -20 kHz 0,853 dB . THD +N @250 W RMS 0.3498% 1 Vrms Input sensitivity

Preamp input impedance 41 kΩ

Amplifier output impedance 11m Ω f < 1kHz. 35m Ω f < 20kHz

Damping factor (8Ω) >720 Amplifier current limit 20 A Efficiency (amp only) 92% Efficiency (amp+preamp) 90.33%

Volume Controller Analogical transistors switching ultra-low distortion medical Thin Film resistors network, independent circuit with low resistance military locking connector. Available in two version:

Low ouput on the first 10 pos Medium ounut on the first 10 pos

Recommended JJTESLA 1x 5AR4 / GZ34,1x 12AX7, 2x 6V6G, 1x 0B2

Eon Link no noise proprietary link

Using Rj45 Cat5 shielded cables

Bluetooth, LED's, microprocessors

10 of which 4 of Kelvin type regula-

15 secondary windings in 3 transformers for a total of 1085 VA in steel and

tions in discrete components

mu-metal internal casing

5 minutes minimum / 24 hours optimum

Infrared and Bluetooth via EonArt API for

Distortion, volume controller, min.level 0.37% Distortion, volume controller, max.level

Pre-amp tubes (2x) Recommended E88CC JJTESLA

Power supply tubes (5x)

Soft-start & Pre-heat

Remote turn-on & control

Links and control between multiple Boson

Cooling Protection mechanisms Thermal Excess Over current from internal source

Over voltage from internal source

Fuses Self-diagnosis

DC power supplies

Power supplies

AC filament power supplies Transformers

Maximum powerconsumption Inrush power consumption Softstart

Idle power consumption Supply voltage factory set

1085 W 2.23 A / 274 W

Total of 13

Yes 2.46 W

Americas, Europe, others AC mains input IEC with a two (2) meters Supra Lorad

Weight (per unit) 83.2 lbs/37.74 kg

Dimensions (Wx HxD) 438 mm x 435 mm x 320 mm

EONART

Operatingmode Integrated Amplifier, home cinema, Home Cinema Direct (preamp bypass) +Volume Direct (preamp bypass) +Volume

Environmental responsibility

board holding the wearable components. 8/10 -Specialist required Repair Index Life Cycle 50 years when Recommended Scheduleis

All-component replacement modules and

5 year calendar with the use of a circuit

adhered to.

Warranty Full product 10 YEARs -Full product Wearables components board 5 YEAR's Recommended schedule provided

Inputs

4 x WBT RCA mono External power supply support

Double (2) shielded chrome and cadmium metal alloy 10 pins circular locking military connectors for a RESERVE external power supply Lundahl transformer input line splitter on 2 WBT Outputs

Low lightmode

Always ON / 10 sec-delay front only or back and front Qty of printed circuit boards Eight (8x) Board thickness 2.5 mm (twice the industry standard)

Qty of layers Board colour Ten (10x) Reflective blue

Thickness of copper track 70 micron copper for each layer Auxiliary supply filter Medical grade, IEC60601-1 Microprocessors Three (3), 1x control, 2x sound parameters I2C, 100 kbit/s Internal network

Shielding Faraday cage in sensible zone and Antistatic windings on transformers

Signal capacitors Amplifier capacitive reserve

Amtrans, Audyn, Clarity, Duelund, Solen Mainly Mundorf >122,293 μF Internal cabling Tin plated OFC Supra Ply and Eff, High Voltage and temperature silicon insulated tin plated OFC, Supra Lorad 3 x 1.5 mm tin

plated OFC

Audio Connectors WBT Cu Nextgen, Neutrik heat resistant XLR

> Casing Brushed aluminium -7 mm alloy chassis with quick access rail system; Faraday cage effect, white enamelled 19 mm solid front panel

RAL color available in option

Access Front access drawer-motion access Rear lock with key

Base

7 mm Brushed aluminium alloy on 20 mm Labradorite semi-precious stone; Soundcare feet. Microphonic vibration neutralizer

Assembly Handmade in Canada by Eon Art Handmade finishand assembly by Oracle Casing assembly Audio Technologies Pelican Protector 673 x 673 x 641mm

Packaging Quality control Musical quality Documentation

Five-level procedure Product certification Audio Precision and Rigol analysers Listening session for each product Documented and signed by the various stakeholders in a certificate to the owner located in an hardcover user manual. 50 unitsper year, numbered edition

Availability

Sold by set of 2, 4 or 6

Stéphane Hautcoeur President, EON Art Canada Inc. Founder, CTO www.eon-art.com info@eon-art.com

Eon Art Canada Inc. 273 Boul, Pabos Chandler, QC G0C 2H0, Canada